# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : BIFLEX AQUAMAX

Other means of identification : BIFENTHRIN 100 G/L SC

Recommended use of the chemical and restrictions on use

Recommended use : Termiticide and insecticide.

Restrictions on use : Use as recommended by the label.

Manufacturer or supplier's details

Company : FMC Australasia Pty Ltd

Address : Building B, Level 2, 12 Julius Avenue,

North Ryde NSW 2113

Telephone : +6161029887900

Emergency telephone number : For leak, fire, spill or accident emergencies, call:

1800 033 111 (Ixom)

Medical emergency:

1 800 033 111 (Transport and 24 h Medical information)

### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Acute toxicity (Oral) Category 4

Acute toxicity (Inhalation) Category 4

Serious eye damage/eye irri-

tation

: Category 1

Skin sensitisation : Category 1

Consolitio tannot annon taviality

repeated exposure

Specific target organ toxicity - Category 2 (Nervous system)

## **GHS** label elements

# **BIFLEX AQUAMAX**



Version **Revision Date:** SDS Number: Date of last issue: 30.07.2021 31.07.2021 50001562 Date of first issue: 30.07.2021 1.1

Hazard pictograms







Signal word Danger

H302 + H332 Harmful if swallowed or if inhaled. Hazard statements

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H373 May cause damage to organs (Nervous system) through

prolonged or repeated exposure.

Precautionary statements

Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

#### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P363 Wash contaminated clothing before reuse.

# Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards which do not result in classification

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
bifenthrin (ISO)	82657-04-3	>= 1 -< 10
propane-1,2-diol	57-55-6	< 10

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021 1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

**SECTION 4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed or if inhaled.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

**SECTION 5. FIREFIGHTING MEASURES** 

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical

Foam

Unsuitable extinguishing

media

High volume water jet

High volume water jet

Specific hazards during fire- : Do not allow run-off from fire fighting to enter drains or water

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021 50001562 Date of first issue: 30.07.2021 1.1 31.07.2021

fighting courses.

Hazardous combustion prod- :

ucts

Thermal decomposition can lead to release of irritating gases

and vapours.

Halogenated compounds

Carbon oxides

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

•3Z Hazchem Code

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

**Environmental precautions** Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

To avoid spills during handling keep bottle on a metal tray. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

# **BIFLEX AQUAMAX**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.07.2021

 1.1
 31.07.2021
 50001562
 Date of first issue: 30.07.2021

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
propane-1,2-diol	57-55-6	TWA (partic-	10 mg/m3	AU OEL
		ulate)		
		TWA (Total	150 ppm	AU OEL
		(vapour and	474 mg/m3	
		particles))		

### Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable per-

sonal respiratory protection and protective suit.

No personal respiratory protective equipment normally re-

quired.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate,

butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

Colour : white, opaque

Odour : mild, like soap

pH : not determined

Melting point/range : not determined

Boiling point/boiling range : not determined

Relative density : 1.02

Bulk density : not determined

Solubility(ies)

Water solubility : not determined

Viscosity

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : Non-oxidizing

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability: No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : Protect from frost, heat and sunlight.

No data available

Incompatible materials : Strong oxidizing agents

Strong acids Strong bases

Not applicable

Hazardous decomposition

products

Stable under recommended storage conditions.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

Harmful if swallowed or if inhaled.

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021 1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

**Product:** 

Acute oral toxicity : LD50 (Rat, male and female): 531 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): 4.94 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Remarks: Based on data from similar materials

**Components:** 

bifenthrin (ISO):

Acute oral toxicity : LD50 (Rat): 53.4 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 0.8 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

LC50 (Rat, male): 1.01 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

propane-1,2-diol:

Acute oral toxicity : LD50 (Rat, male and female): 22,000 mg/kg

Acute inhalation toxicity : LC0 (Rabbit): 31.7 mg/l

Exposure time: 2 h
Test atmosphere: vapour
Remarks: no mortality

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

Remarks : Extremely corrosive and destructive to tissue.

# **BIFLEX AQUAMAX**



VersionRevision Date:SDS Number:Date of last issue: 30.07.20211.131.07.202150001562Date of first issue: 30.07.2021

**Components:** 

bifenthrin (ISO):

Species : Rabbit

Method : EPA OPP 81-5
Result : No skin irritation

propane-1,2-diol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit

Result : Irreversible effects on the eye

Remarks : Based on data from similar materials

Remarks : May cause irreversible eye damage.

**Components:** 

bifenthrin (ISO):

Species : Rabbit

Result : No eye irritation Method : EPA OPP 81-4

propane-1,2-diol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

**Product:** 

Species : Guinea pig

Result : May cause sensitisation by skin contact.
Remarks : Based on data from similar materials

Remarks : Causes sensitisation.

# **BIFLEX AQUAMAX**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.07.2021

 1.1
 31.07.2021
 50001562
 Date of first issue: 30.07.2021

**Components:** 

bifenthrin (ISO):

Method : OECD Test Guideline 406

Result : May cause sensitisation by skin contact.

propane-1,2-diol:

Test Type : Maximisation Test
Species : Guinea pig
Result : negative

**Chronic toxicity** 

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

bifenthrin (ISO):

Genotoxicity in vitro : Test system: Chinese hamster ovary cells

Result: negative

Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration

Species: Rat Result: negative

propane-1,2-diol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

**Components:** 

bifenthrin (ISO):

Species : Rat
Application Route : Oral
Exposure time : 2 Years

NOAEL : 3 mg/kg bw/day

Result : negative

Species : Mouse Application Route : Oral

Exposure time : 18 month(s)

NOAEL : 7.6 mg/kg bw/day

Result : positive

Carcinogenicity - Assess- : Weight of evidence does not support classification as a car-

# **BIFLEX AQUAMAX**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.07.2021

 1.1
 31.07.2021
 50001562
 Date of first issue: 30.07.2021

ment cinogen

propane-1,2-diol:

Species : Rat
Application Route : Oral
Exposure time : 2 Years
Result : negative

Reproductive toxicity

Not classified based on available information.

**Components:** 

bifenthrin (ISO):

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: Oral

General Toxicity - Parent: NOAEL: 3 mg/kg bw/day General Toxicity F1: NOAEL: 3 mg/kg bw/day

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Oral

General Toxicity Maternal: NOAEL: 2.7 mg/kg bw/day

Symptoms: Maternal effects Result: No teratogenic effects

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

propane-1,2-diol:

Effects on fertility : Test Type: reproductive and developmental toxicity study

Species: Mouse Application Route: Oral Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 414

Result: Animal testing did not show any effects on fertility.

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

**Components:** 

bifenthrin (ISO):

Remarks : No significant adverse effects were reported

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

### STOT - repeated exposure

May cause damage to organs (Nervous system) through prolonged or repeated exposure.

### **Components:**

bifenthrin (ISO):

Target Organs : Nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 1.

### Repeated dose toxicity

**Components:** 

bifenthrin (ISO):

Species : Rat

LOAEL : 7 - 9 mg/kg

Application Route : Oral Exposure time : 90 d

propane-1,2-diol:

Species : Rat, male and female

NOAEL : 1,700 mg/kg

Application Route : Oral Exposure time : 2 Years

Species : Rat, male and female

NOAEL : 1,000 mg/kg
LOAEL : 160 mg/kg
Application Route : Inhalation
Exposure time : 90 Days

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### bifenthrin (ISO):

The substance does not have properties associated with aspiration hazard potential.

### **Further information**

**Product:** 

Remarks : No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

### **Components:**

# bifenthrin (ISO):

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.15

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.11

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (algae): 0.822 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox-

icity)

10,000

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.12

Exposure time: 21 d

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Crustaceans): 0.0013

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

100,000

Toxicity to soil dwelling or-

ganisms

(Eisenia fetida (earthworms)): > 18.9 mg/kg

Exposure time: 14 d

Toxicity to terrestrial organ-

isms

LD50 (Colinus virginianus (Bobwhite quail)): 1,800 mg/kg

LD50 (Apis mellifera (bees)): 0.015 µg/Bee

Remarks: Contact

LD50 (Apis mellifera (bees)): 0.1 µg/Bee

Remarks: Oral

propane-1,2-diol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

(Mysidopsis bahia (opossum shrimp)): 18,800 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 34,100

mg/l

Exposure time: 48 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 13,020 mg/l

Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 20,000 mg/l

Exposure time: 18 h

# **BIFLEX AQUAMAX**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.07.2021

 1.1
 31.07.2021
 50001562
 Date of first issue: 30.07.2021

Persistence and degradability

**Components:** 

bifenthrin (ISO):

Biodegradability : Result: Not readily biodegradable.

propane-1,2-diol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 23.6 % Exposure time: 64 d

Method: OECD Test Guideline 306

Bioaccumulative potential

**Components:** 

bifenthrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,414

Remarks: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is possible.

See section 9 for octanol-water partition coefficient.

propane-1,2-diol:

Partition coefficient: n-

octanol/water

: log Pow: -1.07

Mobility in soil

**Components:** 

bifenthrin (ISO):

Distribution among environ-

mental compartments

Remarks: immobile

Stability in soil : Dissipation time: 86 d

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021 1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Bifenthrin)

Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Bifenthrin)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

: 964

964

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Bifenthrin)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

# Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

**ADG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Bifenthrin)

Class : 9 Packing group : III

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

Labels : 9 Hazchem Code : •3Z

Remarks : Not subject to the ADG Code when transported by Road or

Rail in Australia, in packages 500kg(L) or less

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mix-

Standard for the Uniform

Scheduling of Medicines and

**Poisons** 

: Schedule 6

Prohibition/Licensing Requirements : There is no applicable prohibition,

authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-

tions.

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

2-METHYLBIPHENYL-3-YLMETHYL (Z)-(1RS,3RS)-3-(2-

CHLORO-3,3,3-TRIFLUOROPROP-1-ENYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE

Smectite-group minerals

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

# **BIFLEX AQUAMAX**



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.07.2021

 1.1
 31.07.2021
 50001562
 Date of first issue: 30.07.2021

NZIoC : Not in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**

Revision Date : 31.07.2021

Date format : dd.mm.yyyy

### Full text of other abbreviations

AU OEL : Australia. Workplace Exposure Standards for Airborne Con-

taminants.

AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative: WHMIS - Workplace Hazardous Materials Information System

### **Disclaimer**

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein re-

# **BIFLEX AQUAMAX**



Version Revision Date: SDS Number: Date of last issue: 30.07.2021
1.1 31.07.2021 50001562 Date of first issue: 30.07.2021

lates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

**AU / 6N**